# NSN 5930-00-881-1364

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-881-1364

# Body Style:

Hole mounted

#### Hazardous Locations/environmental Protection:

Dustproof

# **Overall Length:**

1.250 inches

### Center To Center Distance Between Mounting Facilities Parallel To Length:

0.520 inches

#### **Overall Height:**

0.594 inches

#### **Overall Width:**

0.688 inches

#### Body Length:

1.250 inches

#### Body Width:

0.500 inches

# Body Height:

\_\_\_\_\_

# 0.500 inches

Case Material:

Plastic

#### **Unthreaded Mounting Hole Diameter:**

0.101 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Height:

0.312 inches

#### Actuator Length:

0.250 inches

#### **Actuator Style:**

Rectangular

#### **Actuator Height:**

0.094 inches

#### Actuator Width:

0.297 inches

#### **Actuator Free Position Height:**

0.150 inches

#### Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

#### Inclosure Type:

Fully enclosed

### Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

## Switch Release Force:

4.0 ounces

# NSN 5930-00-881-1364

Sensitive Switch - Page 2 of 2



Switch Actuating Force:

13.0 ounces

#### **Actuator Movement:**

Between 0.050 pretravel inches and 0.015 overtravel inches and 0.020 differential inches

#### Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes inductive dc and 10.000 amperes inductive ac

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0