

View Online at <https://aerobasegroup.com/nsn/5930-00-881-9711>

**Thread Class:**

3b single pressure connection

**Overall Length:**

1.938 inches

**Overall Width:**

3.625 inches

**Body Diameter:**

3.000 inches

**Mounting Slot Width:**

0.219 inches

**Body Length:**

1.438 inches

**Unthreaded Mounting Hole Diameter:**

0.219 inches

**Longest Horizontal Distance Between Mounting Centers:**

1.500 inches

**Longest Vertical Distance Between Mounting Centers:**

3.000 inches

**Pressure Switch Type:**

Gage

**Operating Temperature Rating:**

Between 125.0 degrees fahrenheit and 175.0 degrees fahrenheit

**Mounting Method:**

Slot and unthreaded hole

**Features Provided:**

Electrical box connector

**Thready Qty Per Inch (tpi):**

20 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

200.00 pounds per square inch gage

**Thread Size:**

0.4375 inches single pressure connection

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Sensing Element Burst Pressure:**

300.00 pounds per square inch gage

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

2.0 amperes resistive load second voltage and 2.0 amperes inductive load second voltage and 2.0 amperes lamp load second voltage

**Contact Adjustability:**

Deactuation point adjustable, preset and actuation point adjustable, preset

**Contact Adjustment Range:**

+5.00/+70.00 actuation point pounds per square inch and +5.00/+70.00 deactuation point pounds per square inch

**Contact Stimulus Rating:**

65.00 actuation point pounds per square inch and 10.00 differential point pounds per square inch

**Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

**Pressure Connector Type:**

Double compression, threaded internal single connection

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Cylindrical w/mounting lugs

**Thread Series Designator:**

Unf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A048b0