

View Online at <https://aerobasegroup.com/nsn/5930-00-881-9711>

Thread Class:

3b single pressure connection

Overall Length:

1.938 inches

Overall Width:

3.625 inches

Body Diameter:

3.000 inches

Mounting Slot Width:

0.219 inches

Body Length:

1.438 inches

Unthreaded Mounting Hole Diameter:

0.219 inches

Longest Horizontal Distance Between Mounting Centers:

1.500 inches

Longest Vertical Distance Between Mounting Centers:

3.000 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between 125.0 degrees fahrenheit and 175.0 degrees fahrenheit

Mounting Method:

Slot and unthreaded hole

Features Provided:

Electrical box connector

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

200.00 pounds per square inch gage

Thread Size:

0.4375 inches single pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

300.00 pounds per square inch gage

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

2.0 amperes resistive load second voltage and 2.0 amperes inductive load second voltage and 2.0 amperes lamp load second voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+5.00/+70.00 actuation point pounds per square inch and +5.00/+70.00 deactuation point pounds per square inch

Contact Stimulus Rating:

65.00 actuation point pounds per square inch and 10.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Pressure Connector Type:

Double compression, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/mounting lugs

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0