

View Online at <https://aerobasegroup.com/nsn/5930-00-882-4444>

Hazardous Locations/environmental Protection:

Shock resistant

Overall Length:

6.125 inches

Overall Height:

6.000 inches

Overall Width:

4.750 inches

Unthreaded Mounting Hole Diameter:

0.406 inches single mounting facility and 0.410 inches single mounting facility

Individual Section Quantity:

4

Longest Horizontal Distance Between Mounting Centers:

3.781 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

3.781 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Unthreaded hole single mounting facility

Features Provided:

Actuator knob

Contact Voltage Rating In Volts:

500.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

60.0 amperes resistive load dc at sea level

Style Designator:

Rectangular panel mount

Test Data Document:

81349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-s-15291/9 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0