

View Online at <https://aerobasegroup.com/nsn/5930-00-883-1533>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Explosion proof

**Actuator Style:**

Roller plunger

**Actuator Roller Diameter:**

0.750 inches

**Actuator Roller Width:**

0.312 inches

**Housing Height:**

2.560 inches

**Housing Length:**

3.660 inches

**Housing Width:**

2.015 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Height:**

1.812 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

2.750 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

24.0 ounces

**Actuator Movement:**

0.109 differential inches and 0.250 pretravel inches

**Contact Load Current Rating At Maximum Rated Voltage:**

150.000 milliamperes resistive dc and 10.000 amperes resistive ac

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A053a0