

View Online at <https://aerobasegroup.com/nsn/5930-00-883-1533>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Explosion proof

Actuator Style:

Roller plunger

Actuator Roller Diameter:

0.750 inches

Actuator Roller Width:

0.312 inches

Housing Height:

2.560 inches

Housing Length:

3.660 inches

Housing Width:

2.015 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Height:

1.812 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.750 inches

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

24.0 ounces

Actuator Movement:

0.109 differential inches and 0.250 pretravel inches

Contact Load Current Rating At Maximum Rated Voltage:

150.000 milliamperes resistive dc and 10.000 amperes resistive ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A053a0