NSN 5930-00-883-9729

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-883-9729

g
Body Style:
Hole mounted
Overall Length:
1.940 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 0.990 inches and 1.010 inches
Body Length:
Between 1.937 inches and 1.943 inches
Body Width:
Between 0.687 inches and 0.693 inches
Unthreaded Mounting Hole Diameter:
Between 0.139 inches and 0.142 inches
Actuator Length:
Between 0.187 inches and 0.193 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
Between 1.063 inches and 1.069 inches
Maximum Voltage Rating In Volts:
440.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Thready Qty Per Inch (tpi):
32
Thread Size:
0.138 inches
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained single switch unit
Switch Release Force:
0.5 ounces
Switch Actuating Force:
3.5 ounces
Actuator Movement:
Between 0.469 pretravel inches and 0.600 overtravel inches and 0.085 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
250.000 milliamperes resistive dc and 20.000 amperes resistive ac
Thread Series Designator:
Unc
Terminal Type And Quantity:
3 screw
Shelf Life:

N/a

NSN 5930-00-883-9729

Sensitive Switch - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A053a0