NSN 5930-00-884-0762

Hazardous Locations/environmental Protection:

Sensitive Switch - Page 1 of 2

Body Style:Hole mounted

2 tab, solder lug



View Online at https://aerobasegroup.com/nsn/5930-00-884-0762

Dustproof
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.500 inches
Body Length:
0.781 inches
Body Width:
0.250 inches
Body Height:
0.438 inches
Case Material:
Metal
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Length:
0.125 inches
Actuator Style:
Rectangular
Actuator Height:
0.093 inches
Actuator Width:
0.125 inches
Actuator Free Position Height:
0.406 inches
Maximum Voltage Rating In Volts:
250.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action single switch unit
Switch Release Force:
10.0 grams
Switch Actuating Force:
2.0 ounces
Actuator Movement:
Between 0.045 pretravel inches and 0.012 overtravel inches and 0.020 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
10.000 amperes resistive dc and 10.000 amperes resistive ac
Terminal Type And Quantity:

NSN 5930-00-884-0762

Sensitive Switch - Page 2 of 2



_					
C.	~~	14	I i	ife:	
J.	16			HE.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0