

View Online at <https://aerobasegroup.com/nsn/5930-00-884-2579>

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Overall Length:

1.797 inches

Overall Height:

1.000 inches

Overall Width:

0.938 inches

First Flat Length:

0.281 inches single actuator

Flat Height:

0.188 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.109 inches single actuator

Nonturn Device Radius:

0.375 inches at 3: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 3: 00 o'clock

Operating Temperature Range:

-40.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section rear

Throw Quantity:

4 single section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

45.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Detent Rotational Torque Range:

+1.000/+3.000 inch-pounds single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Special Features:

0.095 diameter roll pin hole located 0.359 in. From mtg surface, include w/item 1 pin-spring p/n ms171504, 1 bracket p/n sm-b-414792

Style Designator:

Circular wafer, bushing mount

Test Data Document:

81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0