

View Online at <https://aerobasegroup.com/nsn/5930-00-884-6686>

**Overall Length:**

1.187 inches

**Overall Height:**

0.783 inches

**Body Diameter:**

0.640 inches

**Body Height:**

0.455 inches

**Distance Between Mounting Facility Centers:**

0.937 inches

**Temperature Sensing Element Type:**

Internal sensor

**Mounting Method:**

Bracket

**Features Provided:**

Hermetically sealed case

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

3.0 amperes resistive load first voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

71.00 actuation point degrees celsius and 79.00 actuation point degrees celsius and 61.00 deactuation point degrees celsius and 69.00 deactuation point degrees celsius and 10.00 differential point degrees celsius

**Contact Voltage Rating In Volts:**

30.0 dc at sea level second voltage

**Frequency In Hertz:**

60.0 first voltage

**Media For Which Designed:**

Gas

**Style Designator:**

Disc w/flange

**Test Data Document:**

96906-mil-std-202 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0