

View Online at <https://aerobasegroup.com/nsn/5930-00-885-0346>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Explosion proof and watertight

**Overall Length:**

2.815 inches

**Overall Height:**

Between 0.970 inches and 1.030 inches

**Overall Width:**

Between 0.970 inches and 1.030 inches

**Body Diameter:**

Between 0.970 inches and 1.030 inches

**Bushing Length:**

Between 0.970 inches and 1.030 inches

**Body Length:**

1.415 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.220 inches and 0.280 inches

**Actuator Height:**

0.370 inches

**Actuator Free Position Height:**

Between 1.340 inches and 1.400 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

64.0 ounces

**Switch Actuating Force:**

Between 96.0 ounces and 192.0 ounces

**Actuator Movement:**

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc and 3.000 amperes inductive dc and 4.000 amperes motor dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

6 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0