## NSN 5930-00-885-0826

Pressure Switch - Page 1 of 2

Style Designator:

Cylindrical



View Online at https://aerobasegroup.com/nsn/5930-00-885-0826

Hazardous Locations/environmental Protection:
Weatherproof
Overall Length:
1.870 inches
Overall Height:
1.690 inches
Overall Width:
1.690 inches
Pressure Switch Type:
Gage
Mounting Method:
Inlet connection
Thready Qty Per Inch (tpi):
27 single pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
150.00 pounds per square inch
Thread Size:
0.125 inches single pressure connection
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Screw
Contact Load Current Rating:
4.0 amperes resistive load first voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
4.00 actuation point pounds per square inch and 3.20 deactuation point pounds per square inch and 0.80 differential point pounds per
square inch
Contact Voltage Rating In Volts:
6.0 dc at sea level second voltage
Pressure Connector Type:
External seat-gasket seal, threaded external single connection
Media For Which Designed:
Gas or liquid
Precious Material And Location:
Contacts silver
Precious Material:
Silver

## NSN 5930-00-885-0826

Pressure Switch - Page 2 of 2



T	<b>h</b> r	ead	<b>Series</b>	Design	nator:

Ptf-sae short single pressure connection

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0