NSN 5930-00-885-3806

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-885-3806 **Thread Class:** 2b single mounting facility **Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 2.688 inches **Overall Height:** 4.000 inches **Overall Width:** 4.000 inches **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 1.000 inches single actuator **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 1.678 inches single mounting facility **Longest Vertical Distance Between Mounting Centers:** 1.678 inches single mounting facility **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 single section rear **Throw Quantity:** 72 single section front **Mounting Method:** Bracket single mounting facility and threaded hole single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.138 inches single mounting facility **Contact Voltage Rating In Volts:** 12.0 ac at sea level **Rotor Through Connection Quantity:** 1 single section **Mounting Facility Pattern:** Four position rectangular single mounting facility **Switch Actuator Indexing Position Quantity:**

72 single actuator

Shaft Type:

Round single actuator

NSN 5930-00-885-3806

Rotary Switch - Page 2 of 2



Terminal Type:
Tab, solder lug
Contact Switching Action:
Makes before breaks single section rear
Switch Actuator Positioning Increment:
5.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
0.1 amperes resistive load ac at sea level
Precious Material And Location:
Contact silver
Precious Material:
Silver
Style Designator:
Tap, square frame
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A052b0