NSN 5930-00-885-3806

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-885-3806 **Thread Class:** 2b single mounting facility **Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 2.688 inches **Overall Height:** 4.000 inches **Overall Width:** 4.000 inches **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 1.000 inches single actuator **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 1.678 inches single mounting facility **Longest Vertical Distance Between Mounting Centers:** 1.678 inches single mounting facility **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 single section rear **Throw Quantity:** 72 single section front **Mounting Method:** Bracket single mounting facility and threaded hole single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.138 inches single mounting facility **Contact Voltage Rating In Volts:** 12.0 ac at sea level **Rotor Through Connection Quantity:** 1 single section **Mounting Facility Pattern:** Four position rectangular single mounting facility **Switch Actuator Indexing Position Quantity:**

72 single actuator

Shaft Type:

Round single actuator

NSN 5930-00-885-3806

Rotary Switch - Page 2 of 2



| Terminal Type: |
|--|
| Tab, solder lug |
| Contact Switching Action: |
| Makes before breaks single section rear |
| Switch Actuator Positioning Increment: |
| 5.0 degrees single actuator |
| Switch Actuator Stop Device Type: |
| Fixed stop single actuator |
| Contact Load Current Rating: |
| 0.1 amperes resistive load ac at sea level |
| Precious Material And Location: |
| Contact silver |
| Precious Material: |
| Silver |
| Style Designator: |
| Tap, square frame |
| Thread Series Designator: |
| Unc single mounting facility |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A052b0 |