NSN 5930-00-885-6206

Rotary Switch - Page 1 of 2



930-00-885-6206

| View Online at https://aerobasegroup.com/nsn/s | 59 |
|--|----|
| Thread Length: | |
| 0.250 inches single mounting facility | |
| First Flat Length: | |
| 0.250 inches single actuator | |
| Flat Height: | |
| 0.220 inches single actuator | |
| Shaft Diameter: | |
| 0.250 inches single actuator | |
| Shaft Length: | |
| 0.560 inches single actuator | |
| Individual Section Quantity: | |
| 8 | |
| Switch Contact Basic Design: | |
| Nonpile-up symmetrical | |
| Pole Quantity: | |
| 1 each section rear | |
| Throw Quantity: | |
| 3 each section rear | |
| Mounting Method: | |
| Threaded bushing single mounting facility | |
| Thread Size: | |
| 0.375 inches single mounting facility | |
| Contact Voltage Rating In Volts: | |
| 115.0 ac at sea level | |
| Switch Actuator Indexing Position Quantity: | |
| 3 single actuator | |
| Shaft Type: | |
| Round, flatted single actuator | |
| Terminal Type: | |
| Tab, solder lug | |
| Contact Switching Action: | |
| Breaks before makes each section rear | |
| Switch Actuator Positioning Increment: | |
| 36.0 degrees single actuator | |
| Contact Load Current Rating: | |
| 5.0 amperes resistive load ac at sea level | |
| Thread Series Designator: | |
| Unef single mounting facility | |
| Shelf Life: | |
| N/a | |

Unit Of Measure:

NSN 5930-00-885-6206

Rotary Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A052b0