NSN 5930-00-886-3635

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-886-3635

Thread Class:

3b single pressure connection

Overall Length:

3.400 inches

Overall Height:

2.620 inches

Overall Width:

2.620 inches

Unthreaded Mounting Hole Diameter:

Between 0.219 inches and 0.235 inches

Longest Horizontal Distance Between Mounting Centers:

2.125 inches

Longest Vertical Distance Between Mounting Centers:

2.125 inches

Pressure Switch Type:

Gage

Operating Tempurature Rating:

Between -65.0 degrees fahrenheit and 360.0 degrees fahrenheit

Mounting Method:

Flange and unthreaded hole

Features Provided:

Hermetically sealed case

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

40.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

3 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

2.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

1.00 actuation point pounds per square inch gage and 0.75 deactuation point pounds per square inch gage and 0.25 differential point pounds per square inch gage

NSN 5930-00-886-3635

Pressure Switch - Page 2 of 2



Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0