## NSN 5930-00-886-6266

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-886-6266

Hazardous Locations/anvironmental Protection					
Hazardous Locations/environmental Protection:					
Dustproof					
Overall Length:					
7.438 inches					
Overall Height:					
6.000 inches					
Overall Width:					
4.750 inches					
Unthreaded Mounting Hole Diameter:					
0.406 inches single mounting facility					
Individual Section Quantity:					
5					
Knob Manufacturer Code:					
82121					
Longest Horizontal Distance Between Mounting Centers:					
3.781 inches single mounting facility					
Longest Vertical Distance Between Mounting Centers:					
3.781 inches single mounting facility					
Switch Contact Basic Design:					
Nonpile-up symmetrical					
Pole Quantity:					
1 each section rear					
Throw Quantity:					
2 each section rear					
Mounting Method:					
Bracket single mounting facility and unthreaded hole single mounting facility					
Features Provided:					
Actuator knob					
Contact Voltage Rating In Volts:					
125.0 ac at sea level					
Mounting Facility Pattern:					
Four position rectangular single mounting facility					
Switch Actuator Indexing Position Quantity:					
4 single actuator					
Terminal Type:					
Tab, solder lug					
Contact Switching Action:					
Breaks before makes each section rear					
Switch Actuator Positioning Increment:					
90.0 degrees single actuator					
Contact Load Current Rating:					

60.0 amperes resistive load ac at sea level

## NSN 5930-00-886-6266

Rotary Switch - Page 2 of 2



S	ne	cial	Feature	es:
J	μυ	viai	. catar	<b>5</b> .

Spacer provided

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0