

View Online at <https://aerobasegroup.com/nsn/5930-00-887-0667>

**Unthreaded Mounting Hole Diameter:**

0.229 inches

**Longest Horizontal Distance Between Mounting Centers:**

Between 1.580 inches and 1.600 inches

**Longest Vertical Distance Between Mounting Centers:**

Between 3.360 inches and 3.380 inches

**Pressure Switch Type:**

Absolute

**Operating Temperature Rating:**

Between -65.0 degrees fahrenheit and 180.0 degrees fahrenheit

**Mounting Method:**

Bracket and unthreaded hole

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

40.00 inches of mercury

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary

**Contact Load Current Rating:**

5.0 amperes resistive load single voltage and 2.0 amperes inductive load single voltage

**Contact Adjustability:**

Actuation point not adjustable

**Contact Stimulus Rating:**

6.71 actuation point inches of mercury

**Contact Voltage Rating In Volts:**

28.0 dc at sea level single voltage

**Media For Which Designed:**

Gas

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0