## NSN 5930-00-887-7375

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-887-7375	
Body Style:	
Hole mounted	
Overall Length:	
1.940 inches	
Center To Center Distance Between Mounting Facilities Parallel To Length:	
Between 0.998 inches and 1.002 inches	
Overall Height:	
1.365 inches	
Overall Width:	
Between 0.672 inches and 0.703 inches	
Body Length:	
1.940 inches	
Body Width:	
Between 0.672 inches and 0.703 inches	
Unthreaded Mounting Hole Diameter:	
0.139 inches	
Actuator Style:	
Roller arm	
Actuator Free Position Height:	
0.790 inches	
Actuator Roller Diameter:	
Between 0.175 inches and 0.205 inches	
Actuator Roller Width:	
Between 0.175 inches and 0.205 inches	
Actuator Adapter Style:	
Roller arm	
Maximum Voltage Rating In Volts:	
125.0 ac and 28.0 dc	
Inclosure Type:	
Fully enclosed	
Mounting Method:	
Unthreaded hole	
Features Provided:	
Actuator seal	

#### **Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:** 

4.0 ounces

#### **Switch Actuating Force:**

Between 10.0 ounces and 26.0 ounces

#### **Actuator Movement:**

Between 0.065 pretravel inches and 0.015 overtravel inches and 0.020 differential inches

# NSN 5930-00-887-7375

Sensitive Switch - Page 2 of 2



### **Contact Load Current Rating At Maximum Rated Voltage:**

25.000 amperes resistive dc and 10.000 amperes inductive dc and 1.000 amperes resistive ac and 1.000 amperes inductive ac

**Terminal Type And Quantity:** 

2	_	_		٠.	
٠.٦	. 5		re.	·M	ı

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0