## NSN 5930-00-888-3030



| Rotary Switch - Page 1 of 2                                   |
|---|
| View Online at https://aerobasegroup.com/nsn/5930-00-888-3030 |
| Thread Class:   |
| 2a single mounting facility                                   |
| Thread Length:  |
| 0.375 inches single mounting facility                         |
| Overall Length:   |
| 2.285 inches  |
| Overall Height:   |
| 1.530 inches  |
| Overall Width:  |
| 1.310 inches  |
| Shaft Diameter:   |
| 0.240 inches single actuator and 0.250 inches single actuator |
| Shaft Length:   |
| 0.375 inches single actuator                                  |
| Nonturn Device Radius:  |
| 0.531 inches at 3: 00 o'clock                                 |
| Individual Section Quantity:                                  |
| 2   |
| Nonturn Device Type:  |
| Tab at 3: 00 o'clock  |
| Switch Contact Basic Design:                                  |
| Nonpile-up symmetrical  |
| Pole Quantity:  |
| 1 each section front  |
| Throw Quantity:   |
| 12 each section rear  |
| Mounting Method:  |
| Threaded bushing single mounting facility                     |
| Thread Size:  |
| 0.375 inches single mounting facility                         |
| Contact Voltage Rating In Volts:                              |
|   |

28.0 dc at sea level

**Rotor Through Connection Quantity:** 

1 each section

**Switch Actuator Indexing Position Quantity:** 

12 single actuator

**Shaft Type:** 

Round single actuator

**Terminal Type:** 

Clip

**Contact Switching Action:** 

Breaks before makes each section front

## NSN 5930-00-888-3030

Rotary Switch - Page 2 of 2



## Switch Actuator Positioning Increment: 30.0 degrees single actuator Contact Load Current Rating: 1.0 amperes resistive load ac at sea level Precious Material And Location: Contacts silver Precious Material: Silver Style Designator: Circular wafer, bushing mount Thread Series Designator: Unef single mounting facility Shelf Life: N/a Unit Of Measure:

No

Fiig:

A052b0

Demilitarization: