

View Online at <https://aerobasegroup.com/nsn/5930-00-888-3578>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

2.500 inches

Overall Height:

1.062 inches

Overall Width:

2.578 inches

Bushing Length:

1.000 inches

Body Length:

1.062 inches

Body Width:

1.641 inches

Body Height:

1.062 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

Between 0.240 inches and 0.260 inches

Actuator Height:

0.375 inches

Actuator Free Position Height:

0.375 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

64.0 ounces

Switch Actuating Force:

154.0 ounces

Actuator Movement:

0.040 pretravel inches and 0.030 overtravel inches and 0.250 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.000 amperes inductive dc and 2.400 amperes lamp dc and 4.000 amperes motor dc

Thread Series Designator:

Unef

Terminal Type And Quantity:

1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0