# NSN 5930-00-888-9619

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-888-9619

## **Thread Class:**

2a single mounting facility

## Thread Length:

0.250 inches single mounting facility

# **Overall Length:**

1.453 inches

## **Overall Height:**

1.500 inches

### **Overall Width:**

1.313 inches

#### Shaft Diameter:

0.250 inches single actuator

## Shaft Length:

0.688 inches single actuator

## **Nonturn Device Radius:**

## 0.438 inches at 9:00 o'clock

## Individual Section Quantity:

1

Nonturn Device Type:

Tab at 9: 00 o'clock

## Switch Contact Basic Design:

Nonpile-up symmetrical

# Pole Quantity:

2 single section rear

## **Throw Quantity:**

3 single section rear

## **Mounting Method:**

Threaded bushing single mounting facility

## **Thread Size:**

0.375 inches single mounting facility

## Contact Voltage Rating In Volts:

110.0 ac at sea level

## Switch Actuator Indexing Position Quantity:

3 single actuator

# Shaft Type:

Round single actuator

## **Terminal Type:**

Tab, solder lug

## **Contact Switching Action:**

Breaks before makes single section rear

# Switch Actuator Positioning Increment:

30.0 degrees single actuator

# NSN 5930-00-888-9619

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 150.0 milliamperes resistive load ac at sea level Style Designator: Circular wafer, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A052b0