

View Online at <https://aerobasegroup.com/nsn/5930-00-889-5918>

Thread Class:

2a single mounting facility

Thread Length:

0.370 inches single mounting facility and 0.380 inches single mounting facility

Width Between Flats:

0.187 inches single actuator and 0.189 inches single actuator

Overall Length:

Between 1.468 inches and 1.483 inches

Overall Height:

Between 0.995 inches and 1.000 inches

Overall Width:

Between 0.933 inches and 0.943 inches

First Flat Length:

0.265 inches single actuator and 0.297 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.250 inches single actuator

Shaft Length:

0.718 inches single actuator and 0.733 inches single actuator

Nonturn Device Radius:

0.365 inches at 3:00 o'clock and 0.385 inches at 3:00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 3:00 o'clock

Operating Temperature Range:

-40.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

2 single section rear

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

90.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, parallel flatted, threaded hole single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks single section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Detent Rotational Torque Range:

+1.000/+5.000 inch-pounds single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Test Data Document:

80063-smd415284 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0