NSN 5930-00-889-7775

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-889-7775

Overall Length:
3.250 inches
Overall Height:
3.350 inches
Overall Width:
2.800 inches
Body Height:
2.370 inches
Unthreaded Mounting Hole Diameter:
0.210 inches
Distance Between Mounting Facility Centers:
2.500 inches
Pressure Switch Type:
Differential
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Hermetically sealed case and electrical access port
Thready Qty Per Inch (tpi):
20 all pressure connection
Contact Action Stimulus:
Increase
Thread Size:
0.438 inches single pressure connection
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
2 pole, single throw, normally closed, momentary action
Terminal Type:
Connector, receptacle
Contact Load Current Rating:
2.0 amperes resistive load single voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
35.00 actuation point pounds per square inch and 33.00 deactuation point pounds per square inch and 2.00 differential point pounds per
square inch
Contact Voltage Rating In Volts:
28.0 dc at sea level single voltage
Pressure Connector Type:
Plain, threaded external all connections

Liquid

Media For Which Designed:

NSN 5930-00-889-7775

Pressure Switch - Page 2 of 2



O4 I		
STVID.	11001	gnator:
OLVIC	Dean	giiatoi.

Rectangular

Thread Series Designator:

Unf all pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0