

View Online at <https://aerobasegroup.com/nsn/5930-00-890-4368>

Thread Class:

2a single mounting facility

Thread Length:

0.560 inches single mounting facility

Overall Length:

3.570 inches

Shaft Diameter:

0.310 inches single actuator and 0.314 inches single actuator

Shaft Length:

0.360 inches single actuator and 0.390 inches single actuator

Overall Diameter:

1.780 inches

Nonturn Device Radius:

0.610 inches at 3: 00 o'clock and 0.640 inches at 3: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 3: 00 o'clock

End Application:

Semi-trailer, 5000 gal, refueler, 4x4, m970 trailer, semi, tank; 5000 gal, bulk

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.500 inches single mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Switch Actuator Momentary Position:

Counterclockwise single actuator

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round single actuator

Criticality Code Justification:

Feat

Terminal Type:

Wire lead

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

20.0 amperes resistive load dc at sea level

Special Features:

Shaft has a tapped hole. Weapon system essential

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Snap or line

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0