

View Online at <https://aerobasegroup.com/nsn/5930-00-890-4368>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.560 inches single mounting facility

**Overall Length:**

3.570 inches

**Shaft Diameter:**

0.310 inches single actuator and 0.314 inches single actuator

**Shaft Length:**

0.360 inches single actuator and 0.390 inches single actuator

**Overall Diameter:**

1.780 inches

**Nonturn Device Radius:**

0.610 inches at 3: 00 o'clock and 0.640 inches at 3: 00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Tab at 3: 00 o'clock

**End Application:**

Semi-trailer, 5000 gal, refueler, 4x4, m970 trailer, semi, tank; 5000 gal, bulk

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.500 inches single mounting facility

**Contact Voltage Rating In Volts:**

30.0 dc at sea level

**Switch Actuator Momentary Position:**

Counterclockwise single actuator

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Shaft Type:**

Round single actuator

**Criticality Code Justification:**

Feat

**Terminal Type:**

Wire lead

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

20.0 amperes resistive load dc at sea level

**Special Features:**

Shaft has a tapped hole. Weapon system essential

**Precious Material And Location:**

Contact surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Snap or line

**Thread Series Designator:**

Unf single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0