

View Online at <https://aerobasegroup.com/nsn/5930-00-890-9299>

Thread Class:

2b 2nd mounting facility

Thread Length:

0.656 inches 1st mounting facility

Overall Length:

6.157 inches

Overall Height:

3.983 inches

Overall Width:

4.094 inches

First Flat Length:

0.312 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.624 inches single actuator

Individual Section Quantity:

8

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Facility Circle Radius:

1.468 inches 2nd mounting facility

Mounting Method:

Threaded hole 2nd mounting facility

Thready Qty Per Inch (tpi):

32 2nd mounting facility

Thread Size:

0.375 inches 1st mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level

Mounting Facility Pattern:

Three position circular 2nd mounting facility

Switch Actuator Indexing Position Quantity:

24 single actuator

Shaft Type:

Round, square single actuator

Square Shaft Size:

0.218 inches single actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

15.0 degrees single actuator

Detent Rotational Torque Range:

+75.000/+85.000 inch-ounces single actuator

Contact Load Current Rating:

125.0 milliamperes resistive load ac at sea level

Precious Material And Location:

Contacts gold

Precious Material:

Gold

Style Designator:

Rectangular panel mount

Thread Series Designator:

Unef 1st mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0