NSN 5930-00-890-9325

Rotary Switch - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5930-00-890-9325 |
|---|
| Thread Class: |
| 2b single mounting facility |
| Overall Length: |
| 11.187 inches |
| Overall Height: |
| 2.344 inches |
| Overall Width: |
| 2.250 inches |
| Shaft Diameter: |
| 0.250 inches single actuator |
| Shaft Length: |
| 1.125 inches single actuator |
| Individual Section Quantity: |
| 8 |
| Longest Horizontal Distance Between Mounting Centers: |
| 1.500 inches single mounting facility |
| Longest Vertical Distance Between Mounting Centers: |
| 1.500 inches single mounting facility |
| Switch Contact Basic Design: |
| Nonpile-up symmetrical |
| Pole Quantity: |
| 1 each section front |
| Throw Quantity: |
| 12 each section rear |
| Mounting Method: |
| Bracket single mounting facility and threaded hole single mounting facility |
| Thready Qty Per Inch (tpi): |
| 32 single mounting facility |
| Thread Size: |
| 0.164 inches single mounting facility |
| Contact Voltage Rating In Volts: |
| 125.0 ac at sea level |
| Mounting Facility Pattern: |
| Four position rectangular single mounting facility |
| Switch Actuator Indexing Position Quantity: |
| 12 single actuator |
| Shaft Type: |
| Round single actuator |
| Terminal Type: |
| Tab, solder lug |
| Contact Switching Actions |

Contact Switching Action:

Breaks before makes each section front

NSN 5930-00-890-9325

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

Special Features:

Ninety six dummy terminals twelve each on rear each section

Style Designator:

Tap, square frame

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0