## NSN 5930-00-890-9466

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-890-9466
Overall Length:
6.156 inches
Overall Width:
4.813 inches
Longest Vertical Distance Between Mounting Centers:
1.312 inches
Pressure Switch Type:
Absolute
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Electrical access port
Thready Qty Per Inch (tpi):
18 single pressure connection
Contact Action Stimulus:
Decrease
Proof Pressure:
100.00 pounds per square inch gage
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Four position rectangular
Nonpile-up Contact Arrangement:
2 pole, double throw, both positions maintained
Terminal Type:
Screw
Contact Load Current Rating:
750.0 milliamperes resistive load third voltage
Contact Adjustability:
Deactuation point adjustable
Contact Adjustment Range:
+0.50/+29.00 deactuation point inches of mercury
Contact Adjustment Type:
Internal deactuation point screw
Contact Voltage Rating In Volts:

600.0 ac at sea level fourth voltage

Frequency In Hertz:

60.0 third voltage

Media For Which Designed:

Gas

Style Designator:

Rectangular

## NSN 5930-00-890-9466

Pressure Switch - Page 2 of 2



T	<b>h</b> r	ead	<b>Series</b>	Design	nator:

Npt single pressure connection

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0