

View Online at <https://aerobasegroup.com/nsn/5930-00-892-9714>

**Thread Class:**

2a and 2b

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Submersible

**Overall Length:**

0.670 inches

**Overall Height:**

1.930 inches

**Overall Width:**

0.670 inches

**Bushing Length:**

0.170 inches

**Body Length:**

0.670 inches

**Body Width:**

0.670 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.093 inches

**Actuator Height:**

0.440 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Mounting Surface To Terminal End Distance:**

1.320 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 1.000 amperes inductive dc and 3.000 amperes resistive ac and 2.000 amperes inductive ac

**Precious Material And Location:**

Terminal surfaces gold

**Test Data Document:**

81349-mil-s-8834 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 tab, solder lug

**Specification Data:**

96906-ms24656 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0