NSN 5930-00-892-9886

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-892-9886

Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
4.062 inches
Overall Height:
4.125 inches
Overall Width:
4.375 inches
Individual Section Quantity:
6
Switch Contact Basic Design:
Nonpile-up symmetrical
Mounting Facility Circle Radius:
1.609 inches single mounting facility
Features Provided:
Actuator knob
Thready Qty Per Inch (tpi):
20 single mounting facility
Thread Size:
0.250 inches single mounting facility
Contact Voltage Rating In Volts:
500.0 ac at sea level
Mounting Facility Pattern:
Four position circular single mounting facility
Switch Actuator Indexing Position Quantity:
4 single actuator
Criticality Code Justification:
Zzzy
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section front
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Switch Actuator Stop Device Type:
Adjustable stop single actuator
Contact Load Current Rating:
30.0 amperes resistive load ac at sea level
Special Features:
Auxiliary mounting method, rear support bracket, two 0.312 inchdia mounting holes, 3.812 inches distance between mountinghole centers
Style Designator:

Tap, circuit selector

NSN 5930-00-892-9886

Rotary Switch - Page 2 of 2



Thread Series Designator	T	hread	Series	Design	ator
--------------------------	---	-------	--------	--------	------

Unc single mounting facility

Reference Number Differentiating Characteristics:

Material will be in accordance with ships parts control centeractivity hx quality control, manufacturing and testing specifications

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A052b0