NSN 5930-00-893-1737

Hazardous Locations/environmental Protection:

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-893-1737

Explosion proof			
Overall Height:			
7.219 inches			
Overall Width:			
4.875 inches			
Shaft Length:			
1.468 inches single actuator			
Unthreaded Mounting Hole Diameter:			
0.438 inches single mounting facility			
Individual Section Quantity:			
3			
Knob Manufacturer Code:			
80064			
Knob Manufacturer Part Number:			
815-1853062			
Switch Contact Basic Design:			
Nonpile-up symmetrical			
Pole Quantity:			
2 each section front			
Throw Quantity:			
4 each section front			
Mounting Facility Circle Radius:			
2.688 inches single mounting facility			
Mounting Method:			
Base single mounting facility			
Features Provided:			
Actuator knob and metallic inclosure			
Contact Voltage Rating In Volts:			
120.0 dc at sea level			
Mounting Facility Pattern:			
Four position circular single mounting facility			
Switch Actuator Indexing Position Quantity:			
4 single actuator			
Shaft Type:			
Rectangular/square, threaded hole single actuator			
Square Shaft Size:			
0.250 inches single actuator			
Terminal Type:			
Tab w/screw			
Contact Switching Action:			

Breaks before makes each section front

NSN 5930-00-893-1737

Rotary Switch - Page 2 of 2



Switch Actuator P	ositioning	Increment:
-------------------	------------	------------

45.0 degrees single actuator

Contact Load Current Rating:

5.0 amperes resistive load dc at sea level

Test Data Document:

80064-815-1853062 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0