NSN 5930-00-893-3782

Hazardous Locations/environmental Protection:

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-893-3782

Dustproof
Overall Length:
10.469 inches
Overall Height:
4.750 inches
Overall Width:
4.750 inches
Shaft Diameter:
0.250 inches single actuator
Shaft Length:
0.750 inches single actuator
Unthreaded Mounting Hole Diameter:
0.406 inches single mounting facility and 0.410 inches single mounting facility
Individual Section Quantity:
7
Longest Horizontal Distance Between Mounting Centers:
3.781 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
3.781 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
500.0 ac at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
8 single actuator
Shaft Type:
Round single actuator
Terminal Type:
Tab w/screw
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Switch Actuator Stop Device Type:

60.0 amperes resistive load ac at sea level

Contact Load Current Rating:

Fixed stop single actuator

NSN 5930-00-893-3782

Rotary Switch - Page 2 of 2



STV/IA	LIDEIG	natar.
SIVIE	Desig	Halvi.

Tap, square frame

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0