# NSN 5930-00-893-4250

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-893-4250

# **Thread Class:**

2a single mounting facility

# Thread Length:

0.375 inches single mounting facility

# **Overall Length:**

2.460 inches

# **Overall Height:**

1.500 inches

### **Overall Width:**

1.312 inches

# First Flat Length:

0.500 inches single actuator

# Flat Height:

0.218 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

# Shaft Length:

0.750 inches single actuator

# Individual Section Quantity:

2

Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

1 each section rear

#### Throw Quantity:

6 each section rear

# **Mounting Method:**

Threaded bushing single mounting facility

# Thread Size:

0.375 inches single mounting facility

# Contact Voltage Rating In Volts:

28.0 dc at sea level

# Switch Actuator Indexing Position Quantity:

11 single actuator

# Shaft Type:

Round, flatted single actuator

# **Terminal Type:**

Tab, solder lug

# **Contact Switching Action:**

Makes before breaks each section rear

# Switch Actuator Positioning Increment:

30.0 degrees single actuator

# NSN 5930-00-893-4250

Rotary Switch - Page 2 of 2



**Contact Load Current Rating:** 

1.0 amperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0