NSN 5930-00-893-9438

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-893-9438

| View Online at https://aerobasegroup.com/nsn/5930-00-893-9438 |
|---|
| Body Style: |
| Bushing mounted |
| Hazardous Locations/environmental Protection: |
| Corrosion resistant |
| Overall Length: |
| 0.844 inches |
| Overall Height: |
| 2.640 inches |
| Overall Width: |
| 1.188 inches |
| Body Length: |
| 0.844 inches |
| Body Width: |
| 1.188 inches |
| Actuator Style: |
| Round, flush |
| Actuator Diameter: |
| 1.062 inches |
| Actuator Height: |
| 0.062 inches |
| Actuator Color: |
| White single actuator |
| Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Method: |
| Threaded bushing |
| Features Provided: |
| Actuator seal |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.953 inches |
| Nonpile-up Contact Arrangement: |
| 2 pole, double throw, both positions maintained single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 5.000 amperes resistive dc and 3.000 amperes inductive dc and 3.000 amperes motor dc and 5.000 amperes resistive ac and 3.000 |
| amperes inductive ac and 3.000 amperes motor ac |
| Thread Series Designator: |
| Uns |

6 tab, solder lug

Terminal Type And Quantity:

NSN 5930-00-893-9438

Push Switch - Page 2 of 2



| C | ha | Ιf | 1 | ife | |
|---|-----|----|---|-------|--|
| • | ııe | | _ | .II C | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0