NSN 5930-00-897-5892

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-897-5892
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
4.905 inches
Overall Height:
2.125 inches
Overall Width:
2.000 inches
Shaft Length:
0.500 inches single actuator
Unthreaded Mounting Hole Diameter:
0.187 inches single mounting facility
Individual Section Quantity:
7
Longest Horizontal Distance Between Mounting Centers:
1.437 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
1.790 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Contact Voltage Rating In Volts:
30.0 lowest dc voltage rating at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator
Shaft Type:
Rectangular/square, threaded hole single actuator
Square Shaft Size:
0.250 inches single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Makes before breaks 4th section front
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load highest dc voltage rating at sea level

NSN 5930-00-897-5892

Rotary Switch - Page 2 of 2



Precious Material And Location:
Contact surfaces silver
Precious Material:
Silver
Style Designator:
Tap, circuit selector
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A052b0