# NSN 5930-00-897-6966

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-897-6966

**Overall Length:** 

3.500 inches

**Overall Height:** 

2.000 inches

**Overall Width:** 

2.000 inches

First Flat Length:

0.500 inches single actuator

Flat Height:

0.218 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.156 inches single actuator

**Unthreaded Mounting Hole Diameter:** 

0.187 inches single mounting facility

#### **Individual Section Quantity:**

```
4
```

## Longest Horizontal Distance Between Mounting Centers:

1.437 inches single mounting facility

## Longest Vertical Distance Between Mounting Centers:

1.750 inches single mounting facility

## Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

1 each section front

#### **Throw Quantity:**

5 each section front

## **Mounting Method:**

Unthreaded hole single mounting facility

## **Contact Voltage Rating In Volts:**

30.0 lowest dc voltage rating at sea level

## **Mounting Facility Pattern:**

Four position rectangular single mounting facility

## Switch Actuator Indexing Position Quantity:

6 single actuator

Shaft Type:

Round, flatted single actuator

**Terminal Type:** 

Screw

**Contact Switching Action:** 

Breaks before makes each section front

# NSN 5930-00-897-6966

Rotary Switch - Page 2 of 2



# Switch Actuator Positioning Increment:

45.0 degrees single actuator

# **Contact Load Current Rating:**

5.0 amperes resistive load lowest dc voltage rating at sea level

# Style Designator:

Square wafer, panel mount

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

No

## Fiig:

A052b0