NSN 5930-00-897-8037

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-897-8037

Hazardous L	_ocations/e	nvironmental	Protection:
-------------	-------------	--------------	-------------

Dustproof

First Flat Length:

0.500 inches single actuator

Flat Height:

0.218 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.156 inches single actuator

Unthreaded Mounting Hole Diameter:

0.187 inches single mounting facility

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

1.437 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

0.875 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Mounting Method:

Flange single mounting facility

Contact Voltage Rating In Volts:

125.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5930-00-897-8037

Rotary Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A052b0