NSN 5930-00-897-8412

Sensitive Switch - Page 1 of 2

Between 0.998 inches and 1.002 inches

Overall Length: 1.938 inches

Overall Height: 1.500 inches Overall Width: 0.688 inches Body Length: 1.938 inches Body Width:



View Online at https://aerobasegroup.com/nsn/5930-00-897-8412

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.688 inches	
Body Height:	
1.047 inches	
Unthreaded Mounting Hole Diameter:	
Between 0.139 inches and 0.143 inches	
Actuator Style:	
Roller plunger	
Actuator Free Position Height:	
Between 1.219 inches and 1.266 inches	
Actuator Roller Diameter:	
0.375 inches	
Actuator Roller Width:	
0.156 inches	
Maximum Voltage Rating In Volts:	
250.0 ac and 125.0 dc	
Inclosure Type:	
Fully enclosed	
Mounting Method:	
Unthreaded hole	
Nonpile-up Contact Arrangement:	
1 pole, double throw, both positions maintained single switch unit	
Switch Release Force:	
3.0 ounces	
Switch Actuating Force:	
10.0 ounces	
Actuator Movement:	
Between 0.078 pretravel inches and 0.094 overtravel inches and 0.008 differential inches	3
Contact Load Current Rating At Maximum Rated Voltage:	
500.000 milliamperes resistive dc and 20.000 amperes resistive ac	
Terminal Type And Quantity:	
3 tab, solder lug	

NSN 5930-00-897-8412

Sensitive Switch - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0