

View Online at <https://aerobasegroup.com/nsn/5930-00-897-9315>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Length:

3.062 inches

Overall Height:

1.375 inches

Overall Width:

1.297 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.216 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.375 inches single actuator

Nonturn Device Radius:

0.531 inches at 3:00 o'clock

Individual Section Quantity:

3

Nonturn Device Type:

Tab at 3:00 o'clock

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section rear

Throw Quantity:

3 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

60.0 degrees single actuator

Detent Rotational Torque Range:

+1.000/+8.000 inch-pounds single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

70.0 milliamperes resistive load ac at altitude

Precious Material And Location:

Terminals and contact surfaces silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0