

View Online at <https://aerobasegroup.com/nsn/5930-00-899-2585>

Thread Class:

2b all threaded hole

Hazardous Locations/environmental Protection:

Moisture resistant

Overall Length:

4.281 inches

Overall Height:

1.750 inches

Overall Width:

1.750 inches

Body Length:

3.656 inches

Longest Horizontal Distance Between Mounting Centers:

1.085 inches

Shortest Horizontal Distance Between Mounting Centers:

Between 0.536 inches and 0.546 inches

Longest Vertical Distance Between Mounting Centers:

Between 1.227 inches and 1.247 inches

Temperature Sensing Element Type:

Expanding shell

Mounting Method:

Flange and threaded hole

Features Provided:

Tamper proof cap

Thready Qty Per Inch (tpi):

32 all threaded hole

Contact Action Stimulus:

Increase

Thread Size:

0.164 inches all threaded hole

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Wire lead

Contact Load Current Rating:

5.0 amperes resistive load second voltage

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Range:

+32.00/+200.00 actuation point degrees fahrenheit

Contact Adjustment Type:

External actuation point screw

Contact Stimulus Rating:

115.00 actuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level third voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Unc all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0