

View Online at <https://aerobasegroup.com/nsn/5930-00-899-6784>

Body Style:

Hole mounted

Overall Length:

0.781 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.370 inches and 0.380 inches

Overall Height:

0.484 inches

Overall Width:

0.250 inches

Body Length:

Between 0.766 inches and 0.797 inches

Body Width:

Between 0.234 inches and 0.266 inches

Body Height:

Between 0.328 inches and 0.344 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.088 inches

Actuator Style:

Round

Actuator Diameter:

0.046 inches

Actuator Free Position Height:

0.360 inches

Maximum Voltage Rating In Volts:

125.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

Between 3.0 ounces and 5.0 ounces

Actuator Movement:

Between 0.030 pretravel inches and 0.005 overtravel inches and 0.004 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

1.500 amperes resistive dc and 5.000 amperes resistive ac

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0