

View Online at <https://aerobasegroup.com/nsn/5930-00-899-7202>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Submersible

Overall Length:

1.346 inches

Overall Height:

2.909 inches

Overall Width:

1.680 inches

Bushing Length:

Between 0.427 inches and 0.447 inches

Body Length:

1.346 inches

Body Width:

1.680 inches

Body Height:

1.390 inches

Actuator Style:

Round

Actuator Diameter:

0.430 inches

Actuator Height:

Between 1.035 inches and 1.129 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Actuator Position-locking Relationship:

Up position locked in and out and down position no locking action

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

12.000 amperes inductive dc and 5.000 amperes lamp dc and 20.000 amperes resistive dc and 15.000 amperes inductive ac and 4.000 amperes lamp ac and 20.000 amperes resistive ac

Test Data Document:

81349-mil-s-3950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

12 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0