

View Online at <https://aerobasegroup.com/nsn/5930-00-899-7788>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Moisture proof

Overall Length:

1.320 inches

Overall Width:

0.890 inches

Bushing Length:

0.470 inches

Body Length:

1.320 inches

Body Width:

0.890 inches

Body Height:

1.100 inches

Actuator Style:

Round

Actuator Diameter:

0.245 inches

Actuator Height:

1.020 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Maximum Voltage Rating In Volts:

230.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

500.000 milliamperes resistive dc and 6.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0