

View Online at <https://aerobasegroup.com/nsn/5930-00-899-8601>

Hazardous Locations/environmental Protection:

Weatherproof

Overall Length:

2.500 inches

Overall Height:

1.870 inches

Overall Width:

1.870 inches

Unthreaded Mounting Hole Diameter:

0.257 inches

Distance Between Mounting Facility Centers:

3.000 inches

End Application:

T-39a airplane 43999

Pressure Switch Type:

Differential

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Thready Qty Per Inch (tpi):

20 all pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

200.00 pounds per square inch gage

Thread Size:

0.4375 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

1.0 amperes lamp load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

9.00 actuation point pounds per square inch and 6.00 deactuation point pounds per square inch and 3.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

30.0 dc at sea level first voltage

Pressure Connector Type:

Plain, threaded internal all connections

Media For Which Designed:

Liquid

Style Designator:

Rectangular

Thread Series Designator:

Unf all pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0