

View Online at <https://aerobasegroup.com/nsn/5930-00-899-9023>

**Thread Class:**

2b 2nd mounting facility

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

4.000 inches

**Overall Height:**

4.125 inches

**First Flat Length:**

0.875 inches single actuator

**Shaft Diameter:**

0.375 inches single actuator

**Individual Section Quantity:**

4

**Knob Manufacturer Code:**

82121

**Nonturn Device Type:**

Slotted bushing at 3: 00 o'clock

**Longest Horizontal Distance Between Mounting Centers:**

2.281 inches 2nd mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.281 inches 2nd mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 4th section front

**Throw Quantity:**

2 4th section rear

**Mounting Method:**

Threaded bushing w/panel seal 1st mounting facility

**Features Provided:**

Actuator knob

**Thready Qty Per Inch (tpi):**

20 2nd mounting facility

**Thread Size:**

0.375 inches 1st mounting facility

**Contact Voltage Rating In Volts:**

500.0 ac at sea level

**Switch Actuator Momentary Position:**

Clockwise single actuator

**Mounting Facility Pattern:**

Four position rectangular 2nd mounting facility

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round, flatted, threaded hole single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes 2nd section rear

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Detent Rotational Torque Range:**

+0.500/+9.000 inch-pounds single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

30.0 amperes resistive load dc at sea level

**Special Features:**

First section is blank

**Style Designator:**

Tap, circuit selector

**Thread Series Designator:**

Unef 1st mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0