

View Online at <https://aerobasegroup.com/nsn/5930-00-899-9023>

Thread Class:

2b 2nd mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

4.000 inches

Overall Height:

4.125 inches

First Flat Length:

0.875 inches single actuator

Shaft Diameter:

0.375 inches single actuator

Individual Section Quantity:

4

Knob Manufacturer Code:

82121

Nonturn Device Type:

Slotted bushing at 3: 00 o'clock

Longest Horizontal Distance Between Mounting Centers:

2.281 inches 2nd mounting facility

Longest Vertical Distance Between Mounting Centers:

2.281 inches 2nd mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 4th section front

Throw Quantity:

2 4th section rear

Mounting Method:

Threaded bushing w/panel seal 1st mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

20 2nd mounting facility

Thread Size:

0.375 inches 1st mounting facility

Contact Voltage Rating In Volts:

500.0 ac at sea level

Switch Actuator Momentary Position:

Clockwise single actuator

Mounting Facility Pattern:

Four position rectangular 2nd mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted, threaded hole single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes 2nd section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Detent Rotational Torque Range:

+0.500/+9.000 inch-pounds single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

30.0 amperes resistive load dc at sea level

Special Features:

First section is blank

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unef 1st mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0