

View Online at <https://aerobasegroup.com/nsn/5930-00-900-5758>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Case Material:

Plastic

Actuator Length:

Between 1.555 inches and 1.585 inches

Actuator Style:

Roller arm

Actuator Roller Diameter:

Between 0.720 inches and 0.780 inches

Actuator Roller Width:

Between 0.282 inches and 0.342 inches

Housing Height:

Between 1.720 inches and 1.780 inches

Housing Length:

Between 2.658 inches and 2.718 inches

Housing Width:

Between 0.970 inches and 1.030 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

Between 1.595 inches and 1.655 inches

Maximum Voltage Rating In Volts:

480.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

6.0 ounces

Switch Actuating Force:

18.0 ounces

Actuator Movement:

Between 0.188 pretravel inches and 0.219 overtravel inches and 0.006 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0