## NSN 5930-00-900-5758

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-900-5758

## Body Style:

Hole mounted

#### Hazardous Locations/environmental Protection:

Dustproof

## Case Material:

Plastic

#### Actuator Length:

Between 1.555 inches and 1.585 inches

#### Actuator Style:

Roller arm

Actuator Roller Diameter:

Between 0.720 inches and 0.780 inches

#### Actuator Roller Width:

Between 0.282 inches and 0.342 inches

#### Housing Height:

Between 1.720 inches and 1.780 inches

## Housing Length:

Between 2.658 inches and 2.718 inches

#### Housing Width:

Between 0.970 inches and 1.030 inches

## Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

Between 1.595 inches and 1.655 inches

#### Maximum Voltage Rating In Volts:

480.0 ac and 250.0 dc

#### Inclosure Type:

Fully enclosed

#### **Features Provided:**

Actuator seal

#### Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

#### Switch Release Force:

6.0 ounces

#### Switch Actuating Force:

18.0 ounces

#### **Actuator Movement:**

Between 0.188 pretravel inches and 0.219 overtravel inches and 0.006 differential inches

#### Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

## Terminal Type And Quantity:

3 screw

## Shelf Life:

N/a

# NSN 5930-00-900-5758

Sensitive Switch - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

