## NSN 5930-00-900-5758

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-900-5758

View Online at https://aerobasegroup.com/nsn/5930-00-900-5758
Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Case Material:
Plastic
Actuator Length:
Between 1.555 inches and 1.585 inches
Actuator Style:
Roller arm
Actuator Roller Diameter:
Between 0.720 inches and 0.780 inches
Actuator Roller Width:
Between 0.282 inches and 0.342 inches
Housing Height:
Between 1.720 inches and 1.780 inches
Housing Length:
Between 2.658 inches and 2.718 inches
Housing Width:
Between 0.970 inches and 1.030 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
Between 1.595 inches and 1.655 inches
Maximum Voltage Rating In Volts:
480.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained single switch unit
Switch Release Force:
6.0 ounces
Switch Actuating Force:
18.0 ounces
Actuator Movement:
Between 0.188 pretravel inches and 0.219 overtravel inches and 0.006 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
250.000 milliamperes resistive dc and 15.000 amperes resistive ac
Terminal Type And Quantity:
3 screw
Shelf Life:
N/a

N/a

## NSN 5930-00-900-5758

Sensitive Switch - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A053a0